

Switch Disconnector Fuse







3KL8

- Range 20 800A
- Available in 2P, TP, TPN and TPSN versions
- Suitable for use in motor
 Feeder as well as Power distribution feeder
 applications



3KA8

- Range 63 1600A
- Available in TPN version
- Suitable for use in motor
 Feeder as well as Power distribution feeder
 applications



Fuse



Siemens Fuse Range



3NA7

- Range 2 A to 800 A
- DIN Fuse
- Unique Dual indication
- High breaking capacity
 - 120 kA



3NW

- Range 2 A to 800 A
- BS Fuse
- Central, Offset & Blade
- Breaking capacity 80kA



SITOR Fuses

- Range 16 A to 800 A
- Semiconductor fuse
- Fast Acting for thyristor protection

Siemens Fuse Range



3KL8

- Range 20 800A
- Available in 2P, TP, TPN and TPSN versions
- Suitable for use in motor
 Feeder as well as Power distribution feeder
 applications



3KA8

- Range 63 1600A
- Available in TPN version
- Suitable for use in motor
 Feeder as well as Power distribution feeder
 applications



An ISO 27001:2013 Certified Company

Network Techlab (I) Pvt. Ltd.

41, Sarvodaya Industrial Estate, Opp. Paper Box, Off. Mahakali Caves Road, Andheri East, Mumbai - 400093, India.

Tel: 022-6681 4101 | Email: info@netlabindia.com | Web: www.netlabindia.com

Our Presence: Mumbai | Navi Mumbai | Ahmedabad | Vadodara | Vapi | Pune | Bangalore | Chennai | Goa | Delhi