

Overload Relays

SIRIUS Thermal Overload Relays

3RU21 1



(Direct Operated)

3RU21 2



(Direct Operated)

3RU11 3



(Direct Operated)

3RU11 4



(Direct Operated)

3RU21 5



(CT Operated)

3RU21 6/7



(CT Operated)

Complete protection for motors up to 250 kW !

SIRIUS Microprocessor Based Relays



3RB20



3RB21



**3RB22 (Monostable)
3RB23 (Bistable)**

Features:

- From 0.1 A to 630 A
- CLASS 10 or 20
- Large setting ranges of 1:4
- Low power loss

Additional Features:

- From 0.1 A to 630 A
- Adjustable tripping CLASS 5 to 30
- Internal ground-fault detection (Switchable)

▪ Features:

- 0.3 A – 630 A
- Current Measuring Module & Evaluation Unit
- Temperature detection & alarm option available



Adding Values to Work

An ISO 27001:2013 Certified Company

Network Techlab (I) Pvt. Ltd.

41, Sarvodaya Industrial Estate, Opp. Paper Box, Off. Mahakali Caves Road, Andheri East, Mumbai - 400093, India.

Tel: 022-6681 4101 | Email: info@netlabindia.com | Web: www.netlabindia.com

Our Presence: Mumbai | Navi Mumbai | Ahmedabad | Vadodara | Vapi | Pune | Bangalore | Chennai | Goa | Delhi